

SERVICE BRANCHES

LONDON 61 Albert Road North Reigate, Surrey Telephone: Reigate 45731-2-3-4-5

NEWMARKET (Suffolk) 176 Exning Road Newmarket Telephone Newmarket 2539 2632

CHEPSTOW (Mon.) Castleford, Tutshill Chepstow, NP6 7YJ Telephone: Chepstow 2732, 2114

SCOTLAND Industrial Estate Larkhall, Lanarkshire Telephone: Larkhall 882370

N. IRELAND Stanley Harvey & Co. Ltd Clarence Street West Belfast Telephone: Belfast 31057-9 (3 lines)

READING (Berks.) Boulton Road Reading, RG2 OND Telephone: Reading 84258-9

DARLINGTON (Co. Durham) McMullen Road Darlington Darlington 2671, 66939

BIRMINGHAM (Warks.) 1210 Stratford Road Hall Green Birmingham, 28 Telephone: 021-777 7111/3

PRESTON (Lancs.) The Grove, School Lane, Longton, Nr. Preston PR4 4SA Telephone: Longton 2451-2

SHEFFIELD (Yorks.) Rotherham Road, Eckington, S31 9FH Telephone: Telephone: Eckington (Derbyshire) 2373-4

EXETER (Devon) 14 Marsh Green Road Marsh Barton Exeter. EX2 8PG Telephone: Exeter 73882, 54017

TERMS OF BUSINESS: Prices and specifications are subject to alteration without notice and, in the Home Market, our goods ar subject to our Terms of Business as quoted in our Price List. oods are sold

> CHARLES H. PUGH LIMITED P.O. BOX 256

ATCO WORKS, TILTON ROAD BIRMINGHAM 9

Telephone: 021-772 2524 (4 lines) 021-772 2551 021-772 3892

Available from

JAMES UPTON LTD. Printed in England

400m/10/69/J.U.



A guide to the range of 4 TCO



Engine: Powerful 4-stroke, cooled by fan and cowl. Stratter: Sturds recoil. Clutch: Entered to the cowl. Stratter: Sturds recoil. Clutch: Efficie with tough. multi-friction discs. Rear Roller: Fluted rubber covered, we-prose, each section with independent drive. Pool brake to prevent over-turn. Cutting Cylinder: 24" width, 6 heavy duty blacks. Get the tory and, Front brake to prevent over-turn. Cutting Cylinder: 24" width, 6 heavy duty blacks. Get the tory and, Front Roller: Weight: 160 lb. Seat: Comfortable and detectable by single wing nut. Weight: 160 lb. (without seat), Tank Capacity: 44 pints petrol. Fuel Consumption: 14 pints pet hour approx. 24" RIDING MOWER WITH AUTO-STEER SEAT

14 pints per hour approx. 20 Th. All 224 MODELES.

20 Th. All 224 MODELES.

Engines, 9worful 14-stroke, Cooled by fan and cowl. Starter; Slurdy recoil. Cutch: Filted with fought, multi-friction dises, Rew Roller; OV, 1wo-proce with independent drue, 24°, three-proces, each section with independent drue. Cuttles, 24°, three-proces, Roller; Dardy baddes; 68 cuts per yard. From Rollers; Continuous, Weight; 20°, drup baddes; 68 cuts per yard. From Rollers; Continuous, Weight; 20°, drup and processing and proces 20" H.D. and 24" MODELS

Degines: Robust 4-stroke, Air cooled by fan and cowl. Starter: Sidemounted, tecola frames: All steed, Javres 34, 1946. But set down the drive by chain to a wide, traction roller: Cutters: Sturdy cutter arm with care by chain to a wide, traction roller: Cutters: Sturdy cutter arm with replaceable stile section. Height of cut: Independent single leaver in each race for machine; etering on front wheels and each strong on front, but and test of machine; etering on front wheels and coll morticity, Greated and testing on front wheels and adjustable for height: 96 lb. Handles: Tubniar, folding and adjustable for height: 18" POWER-PROPELLED ROTARY MODEL

Suggies: Powerful Kohler IT-1cc. 4-stroke. Cooled by fan and cowl.

Starter: Sturdy recoil. Clutch: Fitted with tough multi-friction discs
located under styled cover pase-packed gear differential.

Cuting Sylmeer; Stromed behind the channease. From Rollers: One-piece
Cuting Sylmeer; Stromed behind the channease. From Rollers: One-piece
metal roller running on ball bearings. Weight: 236 lb.

Tank Capacity: 6 pints petrol. Fuel Consumption: 1½ pints per hour. 30" GARDEN MODEL

This guide can do little more than indicate the scope of a range of mowers whose same has been a household word since 1921. Every model embodies the experience gained over one of the longest histories of power mower manufacture in the world.

Spenares and more detailed literature is available upon request for those Alcos and also for the 20 'Heavy Duty Sidewheel model, 84' fully-powered Traple and Alco Gang Mowers.





12" HAND MOWER

Cutting Cylinder: Running on ball bearings in sealed, grease-packed bearing housings. 12" width, 6 blades, specialised Atco quality and construction. Simple screwdriver adjustment. Transmission: By highest quality roller chains and steel chainwheels. Totally enclosed. Rear Roller: Two-piece with independent drive to each section. Freewheels for drawing machine back easily. Front Rollers: Adjustment by single hand wheel.

PRICE: £13 5 0

12" BATTERY-ELECTRIC MODEL

Motor: Electric G.E.C. Battery: 12 volt. Charger: Incorporated, two types available 200/250 volt or 110/120 volt, off A.C. supply Controls: One-speed. Rear Roller: 12, one piece. Roller Drive Release: For power to cutters only. Cutting Cylinder: 12" width; 5 blades, 74 cuts per yard. Front Rollers: Hardwood, Wing adjusting nuts. Weight: 79 lb.

PRICE: £34 0 0

14" and 17" BATTERY-ELECTRIC MODELS Motor: Electric G.E.C. Battery: 12 volt, Charger: Incorporated, two types available, 200/250 volt or 110/120 volt, off A.C. supply, Controls: Two-speeds. Rear Roller: 14", one piece; 17", two-piece with independent drive to each section. Roller Drive Release: Operated from the handles for power to cutters only.

Cutting Cylinder: 14" and 17" widths, 6 blades, 76 cuts per yard.

Front Rollers: Hardwood 'instant set' for height by single lever and wing nut. Weight: 14", 104 lb. 17", 117 lb.

PRICES: 14" £44 18 0 17" £51 10 0

12", 14", 17" and 20" MODELS

Engine: Sturdy 4-stroke. Air Cooled by fan and cowl. Starter: Recoil. Clutch: Fitted with 2 tough friction discs. Rear Roller: 12"/14" one-piece, 17"/20" two-piece each section with independent drive. Roller Drive Release: Operated from handles for power to cutters only. Cutting Cylinder: 12", 14", 17" and 20" widths, 6 blades, 76 cuts per yard. Front Roller: Hardwood, 'instant set' for height by a single lever and wing nut. Weight: 12", 91 lb. 14", 94 lb. 17", 107 lb. 20", 113 lb. Tank Capacity: 3 pints. Fuel Consumption: 1/2 to 1 pint per hour

PRICES: 12" £32 16 0 17" £51 10 0 14" £39 19 0 20" £60 10 0

18" and 21" ROTARY MODELS Engine: Robust 145-cc 4-stroke. Air cooled by fan and cowl. Starter: Recoil. Frame: All steel. Drive: Direct to Rotary arm with friction safety device. Wheels: With 8" diameter rubber tyres.



12", 14", 17" and 20" Models

18" and 21" Rotary Models Height of Cut: By 'Heightomatic' from 3" to 31'. Four wheels adjusted simultaneously by lever, no tools. Cutters: 'Roto-Lift' balanced rotary cutting arm. Two-knife blades with three cutting edges. Handles: Adjustable for height. Rigid or floating. Weight: 18", 73 lb. 21", 86 lb. Tank Capacity: 41 pints.

PRICES: 18" £36 15 0 21" £43 0 0

28" AND 34" MODELS Engine: Powerful A.V. Mk. 25. Cooled by fan and cowl. Clutch: Metal to metal cone clutch of generous dimensions. Rear Roller: Three-piece with sealed grease-packed gear-differential. Cutting Cylinder: 28" and 34" widths, Six heavy duty blades, 81 cuts per yard. Front Rollers: Aluminium sections with grease-packed bushes.
Starter: Kick starter. Weight: 28", 310 lb.
34", 333 lb. Tank Capacity: 4½ pints petrol. Fuel Consumption: 28", approximately 12 pints per hour; 34", 2 pints per hour approx.

PRICES: 28" £188 0 0 34" £209 0 0

20" 'SPECIAL' MODEL

Engine: Powerful 4-stroke. Air cooled by fan and cowl.
Starter: Recoil. Chitch: Fitted with tough, multi-friction discs.
Cutter (Recoil. Chitch: Fitted with 12 blades, 135 cuts per yard.
Cutter Release: Permitting machine to be driven with cutting cylinder disengaged. Rear Roller: Ywo-piece. Each section with independent drive. Front Roller: Metal. Scraper bar, Front Roller Bracket: Designed to avoid 'scalping' on undulating greens. Power Driven Transport Wheels, Weight: 155 lb. Tank Capacity: 41 pints. Fuel Consumption: 1½ pints per hour approx.

PRICE: £117 10 0

ATCO GANG MOWERS

There are three models available, Model 1, Model 2 and Model 3. Offered in a wide range of combinations they are ideal for the high speed maintenance of large areas. Full details about these and the mounted versions, can be obtained from separate literature (the Atco Model 3 only, is illustrated).



Separate and more detailed literature is available upon request for these Atcos and also for the 20" Heavy Duty Sidewheel model, 84" fully-powered Triple and Atco Gang Mowers.

